

RANGE-R® LINK

Handheld, portable through-wall radar

Range-R® Link, a new version of the L3Harris Range-R®, improves officer even further. With an embedded wireless capability, Range-R Link allows your team to virtually eliminate their exposure to the danger zone surrounding a building, while retaining the handheld capability of Range-R when up-close operations are required.

Range-R Link technology enables remote operational and monitoring of the Range-R sensor via secure Wi-Fi. This enables the Range-R Link, mounted on the Range-R Link monopod, to be strategically positioned against a wall and operated / monitored remotely from a safe location at least 100 meters away. When the Range-R Link app is activated, scans are controlled remotely so the unit can be left for an extended period with occasional scanning of the building interior. A dedicated device* provides this capability in a pocket-sized display. This "virtual sentry" capability minimizes your time in the fatal funnel.

The unit also speeds team communication of the situation at hand by permitting remote viewing of the target information.

A dedicated Wi-Fi network permits another team member to simultaneously see the same information as the operator. Up to four Range-R Link sensors can be viewed and operated from the same remote display.

The Range-R Link is essentially a Range-R with an embedded Wi-Fi functionality. It is available for new purchases or your existing Range-R units can be easily upgraded. The system includes the Range-R Link sensor, monopod and pocket-sized remote display*.

* A specially-programmed Android phone is used for this purpose.



A lightweight handheld radar system designed to detect people through walls and structural barriers made from common building materials.

APPLICATIONS

- > Hostage recovery
- > Tactical entry
- > Search & Rescue
- > Breaching operations
- > Stowaway detection

SPECIFICATIONS		
Unique Features		
Dimensions	8.9" x 4" x 3.8"	22.6 cm x 10.2 cm x 9.4 cm
Weight	1.5 lb, no batteries	0.7 kg, no batteries
Detection Range	50+ feet	15+ meters
Resolution	15.75"	40 cm
Field of View	180 degrees Azimuth	(180 degrees in elevation)
Waveform Type	Stepped-frequency continuous wave (SFCW)	
Bandwidth (BW)	3.1 – 3.34 GHz, 120 discrete frequency steps	
Output Power	32 mW	(+15 dBM)
Power Requirements	4 standard AA batteries (L91 recommended) or Range-R Rechargeable Battery Kit	
Environmental		
Operating Temperature	-4°F to +122°F	-20°C to +50°C
Operating Time with Batteries	~400 scans (Lithium L91)	
(15 – 30 second scan)	<100 scans (alkaline)	
System Components		
> Range-R Link Sensor		
> Monopod and adapter		
> Android remote control device		
> Training CD		
> Environmentally hardened carry case		
Optional		
> Range-R rechargeable battery kit		
Operational Standards		

This device has received certification under the authority of the Federal Communications Commission (FCC).

Licensed non-broadcast station transmitter

YKD-25TWD3000-029



RANGE-R LINK SYSTEM Front Profile



RANGE-R LINK SYSTEM Side Profile

Range-R® Link

Identifier:

Equipment Class:

© 2021 L3Harris Technologies, Inc. | 06/2021

PUBLIC RELEASE via DoD/OSR approval and ITAR 120.11(a)(7). The subject item(s) is public domain material. Cleared by DoD/OSR for public release under 21-S-0747 on Feb. 9, 2021. Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice at L3Harris' discretion. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders.

L3Harris Technologies is an agile global aerospace and defense technology innovator, delivering end-to-end solutions that meet customers' mission-critical needs. The company provides advanced defense and commercial technologies across air, land, sea, space and cyber domains.



1025 W. NASA Boulevard Melbourne, FL 32919 t +1 407 926 1914 FOS.CyTerra@L3Harris.com